



KP 949 FO

TECHNICAL DATA SHEET

Introduction

- Good stock removal rates with very high stability paper backing.
- Longer time life.
- Excellent and fast grinding performance.
- Good finishing grade.



Backing Material	Antistatic "F" weight paper
Bonding	Double resin
Mineral Type	Aluminum Oxide
Coating State	Open coat
Manufacturing Width	1400mm

Available Grits

24	36	40	50	60	80	100	120	150	180	220	240
	●	●	●	●	●	●	●	●	●	●	
280	320	360	400	500	600	800	1000	1200	1500	2000	2500

◀ Rough (Grinding)

Finishing (Polishing) ▶

- Introductory Remarks ● : Standard Grit ▲ : Non Standard Grit (Available under request with a MOQ)

Application

- > Dry use
- > Rough sanding, fine sanding of parquetry

Field

- > Car body
- > Wood
- > Metal

Form

- > Rolls
- > Sheets
- > Discs
- > Belts

Usage



Head Office:

Via Delle Groane, 27/E 20024 Garbagnate M. -Mi- Italy

E-mail: itas.it@itasabrasivi.com

Website: www.itasabrasivi.com

I.T.A.S. ABRASIVES CO., LTD.

Yunxin Avenue, Yungang Road,
414009, Yueyang City, Hunan, China

Tel. +86 0730 3072778 / +86 0730 3072998

E-mail: itas.cn@itasabrasivi.com