




SR 727J flex

TECHNICAL DATA SHEET

Introduction

- > Excellent sanding and finishing by the precisely coated silicon carbide grit.
- > Antistatic treatment.
- > Heat resistant.
- > Extra high tensile strength and elongation.



Backing Material	Flexible poly cotton cloth
Bonding	Double resin
Mineral Type	Silicon carbide
Coating State	Closed coat
Manufacturing Width	1400mm

Available Grits

24	36	40	50	60	80	100	120	150	180	220	240
		△	△	●	●	●	●	●	●	●	●
280	320	360	400	500	600	800	1000	1200	1500	2000	2500
●	●	●	●	△	●	●	●				

◀ Rough (Grinding) Finishing (Polishing) ▶

- Introductory Remarks ● : Standard Grit △ : Non Standard Grit (Available under request with a MOQ)

Application

- > Dry use
- > Grinding, contour grinding and finishing in particular for working of taps and fittings

Field

- > Brass
- > Titanium
- > Glass
- > Non-Ferrous Metal

Form

- > Rolls
- > Narrow belts

Usage



Head Office:
 Via Delle Groane, 27/E 20024 Garbagnate M. -Mi- Italy
 E-mail: itas.it@itasabrasivi.com
 Website: www.itasabrasivi.com

I.T.A.S. ABRASIVES CO., LTD.
 Yunxin Avenue, Yungang Road,
 414009, Yueyang City, Hunan, China
 Tel. +86 0730 3072778 / +86 0730 3072998
 E-mail: itas.cn@itasabrasivi.com