




## KP 815 C

## TECHNICAL DATA SHEET

### Introduction

- Excellent sanding quality by the precisely coated special aluminum oxide grit.
- Sanding options by hand or orbital sander.
- High finishing level for perfect smooth surface.
- Special anti-clogging top coat.



Backing Material:	"C/D"Weight latex paper
Mineral Type:	Aluminum Oxide
Bonding:	Double resin
Coated state:	Open
Jumbo Width:	1400mm

### Available Grits

24	36	40	50	60	80	100	120	150	180	220	240
				●	●	●	●	●	●	●	●
280	320	360	400	500	600	800	1000	1200	1500	2000	2500
●	●	△	●	●	●	△	△				

< Rough (Grinding)

Finishing (Polishing) ▶

- Introductory Remarks ● : Standard Grit △ : Non Standard Grit (Available under request with a MOQ)

### Application

- Wood, Aluminum alloy & Soft metal

### Field

- Aluminum alloy
- Soft metal
- Filler & paint

### Form

- Rolls
- Sheets
- Discs
- Narrow belts

### Usage



Head Office:

Via Delle Groane, 27/E 20024 Garbagnate M. -Mi- Italy

E-mail: [itas.it@itasabrasivi.com](mailto:itas.it@itasabrasivi.com)

Website: [www.itasabrasivi.com](http://www.itasabrasivi.com)

I.T.A.S. ABRASIVES CO., LTD.

Yunxin Avenue, Yungang Road, 414009, Yueyang, Hunan, China.

Tel. +86 0730 3072778 / +86 0730 3072998

E-mail: [itas.cn@itasabrasivi.com](mailto:itas.cn@itasabrasivi.com)